

ERMETIKA EVOLUTION MAX | Single and Double Door Plasterboard

Product Specification

Metal cavity door system made of zinc coated metal panels. Model EVOLUTION MAX : 12 reinforcement bars; reinforced side fit for expansion small blocks, not provided, able to hang wall furniture such as tv, shelves, etc. cavity width mm 58 for finished wall size 155 mm; fit for a single door (EVOLUTION MAX SINGLE DOOR MODEL) or for two opposite doors (EVOLUTION MAX DOUBLE DOOR MODEL). The doors shall be flat and fit for sliding into a pocket wall. Maximum door weight 100Kg.

Passage Opening _____

TECHNICAL SHEET

System components:

- double-staved metal panels DX51 Z100
- 6+6 reinforcement bars "omega" shaped
- pre-assembled top profile with "Easyclip" system and anodised aluminum rail
- 2 spacers with two bendable lips
- 1 standard track kit:

- 2 trolleys with 4 ball bearings 100 kg capacity
- Floor guide for door installation including screws and plugs
- Nuts for trolleys, metal plugs for door hanging
- Nylon door stopper with fixing screws

Set up:

The system that comes mounted is ready for fitting a metal structure for plasterboard already assembled. It is mandatory to keep the system squared and fix it with appropriate tolerance in order to avoid vertical pressure, following accurately the technical instruction provided; after the system is set and plumb, put 12,5 mm plasterboard sheet on regular side, and use on the side fit for loads small blocks for plasterboard, in the right dimension and quantity according to the weight and safety factor stated in the technical information of the supplier. You can put weights on the wall where the door lays when full open such as wall furniture, shelves, etc..

Sliding doors:

wood

Honeycomb door 42 mm max thick, raw finish or with primer, with bottom milling for floor guide.

glass-aluminium

Door panel 40 mm max thick with aluminium frame and glass 6/8 mm inside.

glass

Panel 8/10 mm with clamps for hanging on rail and special floor guide for glass door.

Kit jambs and architraves:

wood

Wood kit for 40 mm max door, equipped of classic or telescopic architrave.
Components : door jambs, architraves, anti-dust brushes and joints for reception jamb.

glass-aluminium

Aluminium kit for 40 mm max door, to be installed with 6 mm glass door through appropriate metal corner brackets following accurately the technical instruction provided.

glass

Wood kit for 10 mm max glass door, ready for lacquering, with telescopic architrave to be cut according to cavity system size and fixed to wall through silicon.

Door hardware:

- Round or oval handle with lock for wooden door:
double lock latch for internal sliding doors: two opposite hooks come out from the front part of the lock, rotating in closing phase to hang the plate. The door can be flush with the wall when full open.
- Round or oval handle, without lock, for wooden door:
round or oval handle to be inserted in suitable millings on doors, fit for interior sliding wood doors without lock. Two opposite side handles and a front little finger pull handle ensure a perfect grab to operate the door. The door can be flush with the wall when full open.
- Handle or handle and lock for glass-aluminium doors:
pre-installed handle integrated on the aluminium structure, with or without lock, square or rectangular shaped. The door can be flush with the wall when full open.
- Handle for glass door:
handle fit for full glass door to be sit on apposite site on the reception side of the panel. The door can be flush with the wall when full open.
- Rod handle for glass door:
rod handle in lucid or satin metal for full glass doors, installed on suitable arrangement on panel to be made on the reception side of the door. The door can't be flush with the wall when full open.

Accessories:

- Soft close EasyStop
- Kit for hanging glass doors;
- Self-closing for single door;
- 120 kg track kit
- Under door profile
- Mag Evo for motorised operation